


## LED PROFILES 9

Product Images

### APPLICATION AREAS:

Office buildings, Retail, Supermarkets, Hospitality, Libraries



Tailor Made

80

CRI



Smart Lighting



CCT Tuning



Dimming  
Optional

## TECHNICAL SPECIFICATIONS

### PRODUCT REFERENCE

<b>ITEM CODE</b>	AR0091616
<b>ENVIRONMENT</b>	Indoor
<b>INSTALLATION</b>	Surface

### CONSTRUCTION AND MATERIALS

<b>SIZE OUT SIDE MM</b>	2000x16x16
<b>CUT OUT SIZE (MM)</b>	-
<b>HOUSING</b>	Extruded Aluminium
<b>LENS / DIFFUSER</b>	High Transmission PMMA
<b>REFLECTOR</b>	N/A
<b>SURFACE FINISH</b>	Anodised/Custom Powder Coated
<b>IP rating</b>	20

### THERMAL MANAGEMENT

<b>HEAT SINK MATERIAL</b>	Aluminium
<b>COOLING TECHNIQUE</b>	Passive

### OPTICAL SYSTEM

<b>BEAM ANGLE</b>	110°
<b>ILLUMINATION MODE</b>	Indirect Lighting
<b>SWIVEL</b>	No

## LIGHT TECHNOLOGY

<b>LED FITTED</b>	NA
<b>DELIVERED LUMENS</b>	NA
<b>CCT (K)</b>	NA
<b>Tunable</b>	NA
<b>LED BINNING</b>	NA
<b>CRI (Ra)</b>	NA
<b>LED LIFE L70</b>	NA
<b>LUMINAIRE</b>	NA
<b>LUMINOUS FLUX</b>	
<b>LUMINOUS EFFICACY</b>	NA

## ELECTRICAL SYSTEM

<b>(UGR)</b>	NA
<b>INPUT VOLTAGE</b>	NA
<b>INPUT POWER</b>	NA
<b>POWER FACTOR</b>	NA
<b>THD</b>	NA
<b>CONTROL GEAR</b>	NA
<b>MOUNTING</b>	
<b>DRIVER PROTECTION</b>	NA
<b>DIMMING</b>	NA
<b>EMERGENCY BATTERY BACKUP</b>	NA


## PACKAGING DETAILS

**PACKING QTY -**


**GROSS WEIGHT -**

**CARTOON SIZE -  
(LXBXH)**

### DIMENSIONS



### PHOTOMETRIC



## **ARCADE LIGHTING INDUSTRIES PVT LTD**

8 Raju industrial estate, Penkar pada, Near  
dahisar check naka, Mira road 401107

**NOTE :** The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability

BP-RV00 AR/FRT/TEC/TDS/01