


## ECLIPS UP DOWN

Product Images

### APPLICATION AREAS:

Office buildings, Retail, Supermarkets, Hospitality, Libraries



CCT Tuning



Linkable



Tailor Made



Low Glare



Burning Hours  
45K

## TECHNICAL SPECIFICATIONS

### PRODUCT REFERENCE

|                     |                   |
|---------------------|-------------------|
| <b>ITEM CODE</b>    | ECLIPS UP DOWN 15 |
| <b>ENVIRONMENT</b>  | Indoor            |
| <b>INSTALLATION</b> | Suspended         |

### CONSTRUCTION AND MATERIALS

|                          |                                     |
|--------------------------|-------------------------------------|
| <b>SIZE OUT SIDE MM</b>  | 599x60x83                           |
| <b>CUT OUT SIZE (MM)</b> | -                                   |
| <b>HOUSING</b>           | Extruded Aluminium                  |
| <b>LENS / DIFFUSER</b>   | High Transmission<br>PMMA           |
| <b>REFLECTOR</b>         | N/A                                 |
| <b>SURFACE FINISH</b>    | White/Black/Custom<br>Powder Coated |
| <b>IP rating</b>         | 30                                  |

### THERMAL MANAGEMENT

|                           |           |
|---------------------------|-----------|
| <b>HEAT SINK MATERIAL</b> | Aluminium |
| <b>COOLING TECHNIQUE</b>  | Passive   |

### OPTICAL SYSTEM

|                          |                          |
|--------------------------|--------------------------|
| <b>BEAM ANGLE</b>        | 110°                     |
| <b>ILLUMINATION MODE</b> | Direct/Indirect Lighting |
| <b>SWIVEL</b>            | No                       |

## LIGHT TECHNOLOGY

|                          |                    |
|--------------------------|--------------------|
| <b>LED FITTED</b>        | Bridgelux          |
| <b>DELIVERED LUMENS</b>  | 1725 / 1650 / 1575 |
| <b>CCT (K)</b>           | 6000 / 4000 / 3000 |
| <b>Tunable</b>           | On Request         |
| <b>LED BINNING</b>       | 3 Step MacAdam     |
| <b>CRI (Ra)</b>          | 80 / 90            |
| <b>LED LIFE L70</b>      | 45,000 HRS         |
| <b>LUMINAIRE</b>         | 2100 / 2025 / 1950 |
| <b>LUMINOUS FLUX</b>     |                    |
| <b>LUMINOUS EFFICACY</b> | 115 Lumens / Watt  |

## ELECTRICAL SYSTEM

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| <b>(UGR)</b>                        | <22                                 |
| <b>INPUT VOLTAGE</b>                | 220 TO 240 Vac                      |
| <b>INPUT POWER</b>                  | 15W (6U+9D)                         |
| <b>POWER FACTOR</b>                 | >0.95                               |
| <b>THD</b>                          | <10%                                |
| <b>CONTROL GEAR</b>                 | IN BUILT                            |
| <b>MOUNTING</b>                     |                                     |
| <b>DRIVER PROTECTION</b>            | OVP, Short Circuit, Surge           |
| <b>DIMMING</b>                      | Phase / Analog / Dali /<br>RF / APP |
| <b>EMERGENCY BATTERY<br/>BACKUP</b> | On Request                          |


## PACKAGING DETAILS

**PACKING QTY -**

**GROSS WEIGHT -**

**CARTOON SIZE -  
(LXBXH)**

### DIMENSIONS



### PHOTOMETRIC



## **ARCADE LIGHTING INDUSTRIES PVT LTD**

8 Raju industrial estate, Penkar pada, Near  
dahisar check naka, Mira road 401107

**NOTE :** The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability

BP-RV00 AR/FRT/TEC/TDS/01