

TURBO TRACK SURFACE

Product Images

APPLICATION AREAS:

Home,Office buildings,Retail,Sports facilities,Studio, Stage,Supermarkets,liberary













TECHNICAL SPECIFICATIONS

PRODUCT REFRENCE

ITEM CODETURBO TRACK SURFACE

12

ENVIRONMENT Indoor INSTALLATION Surface

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM 63 Dia x 140

CUT OUT SIZE (MM) -

HOUSING Extruded Aluminium

LENS / DIFFUSER Tempered Glass
REFLECTOR PC High Purity

Metallised

SURFACE FINISH White/Black/Custom

Powder Coated

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE 15°,24°,36°,60°
ILLUMINATION MODE Direct Lighting
SWIVEL No

LIGHT TECHNOLOGY

LED FITTED Bridgelux

DELIVERED LUMENS 1380 / 1320 / 1260 CCT (K) 6000 / 4000 / 3000

Tunable On Request **LED BINNING** 3 Step MacAdam

CRI (Ra) 80 / 90 **LED LIFE L70** 40,000 HRS

LUMINAIRE 1920 / 1860 / 1800

LUMINOUS FLUX

LUMINOUS EFFICACY 115 Lumens / Watt

ELECTRICAL SYSTEM

NA (UGR)

INPUT VOLTAGE 220 TO 240 Vac

INPUT POWER 12W **POWER FACTOR** >0.95 <10% **THD CONTROL GEAR** IN BUILT

MOUNTING

DRIVER PROTECTION OVP, Short Circuit, Surge **DIMMING**

Phase / Analog / Dali /

RF / APP


EMERGENCY On Request

BATTERY BACKUP


PACKAGING DETAILS

GROSS WEIGHT CARTOON SIZE PACKING QTY (LXBXH)

DIMENSIONS



PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka. Mira road 401107

NOTE: The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers